

RS636-2GF4GT

Guide rail managed industrial Ethernet switch, with 2 Gigabit fiber ports and 4 Gigabit copper ports



- 2 Gigabit fiber ports and 4 Gigabit copper ports are provided
- Fan-free design, operating temperature: -40 ~ 85°C
- IP40-rated protection, shock-resistant aluminum enclosure
- Support for dual power supply redundant backup input, with a wide range of 9-48 VDC
- EMC industrial rating level 4 electromagnetic compatibility standard
- WEB interface, dial switch rapid configuration
- Support for one-button recovery of factory settings
- Support for STP/RSTP ring protection, and SNMP V1/V2c network management platform



Product profile

RS636-2GF4GT is a guide rail managed industrial Ethernet switch that provides 2 Gigabit fiber ports and 4 Gigabit copper ports via a fan-free and low-power design with industrial rating level 4 and IP40-rated protection. Each product, featuring an operating temperature of -40 ~ 85°C, superior solidness, design for network communications in harsh applications, high EMI/EMS protection, has been 100% qualified in aging tests.

Product features

- Support the 802.1Q VLAN of 4K range;
- Support the web page management configuration; and hardware one-button recovery of factory settings
- Dual power inputs with a wide range of 9-48 VDC;
- Dial switches enable ringing and port isolation

For example, STP/RSTP, 802.1Q VLAN, QoS function., port aggregation, port mirroring, loop detection, etc.; support for port configuration, jumbo frame mode, port statistics, speed dial configuration, online upgrade, etc.; support for WEB, SNMP and other access methods. The friendly, simple and convenient interface design of network management system offers a good user experience.

- QoS (IEEE 802.1p and DSCP) improves data transfer certainty;
- Port mirroring feature assists in online troubleshooting and allows for data analysis and monitoring
- Port aggregation increases bandwidth and enhances the reliability of network connection
- Spanning Tree Protocol STP/RSTP ring redundancy
- Port loop detection reduces the impact of access loop on the entire network

Product properties

Applicable standards

IEEE 802.3 10BaseT
IEEE 802.3u 100BaseT
IEEE 802.3z 1000BaseFX and 1000BaseT
IEEE 802.3x flow control
IEEE 802.1d-2004 STP protocol
IEEE 802.1w RSTP protocol
IEEE 802.1p Qos
IEEE 802.1q VLAN
SNMPv1/v2c
HTTP, DHCP Client

Switching feature

Backplane bandwidth: 12 Gbps

List of MAC addresses: 2K

Chip buffer size: 12 KByte

Port

Fiber port: 1000 Mbps

Copper port: 10/100/1000 Mbps self-adaptive, Full/Half duplex mode, MDI/MDI-X supported.

LED indicator: P1, P2, RUN, L/A

Power source requirement

Input voltage: DC 9~48 V (redundancy)

Full-load power consumption: 5W

Input current: Maximum DC current, 400 mA

Physical properties

Enclosure: Aluminum enclosure, IP40-rated protection

Size: 116 × 85 × 37 mm

Weight: 430 g

Mounting method: Guide rail type

Environmental restrictions

Working temperature: -40 ~ 85°C (-40 ~ 185°F)

Storage temperature: -40 ~ 85°C (-40 ~ 185°F)

Relative ambient humidity: 5 ~ 95% (non-condensing)

Standards and certification

EMS:

IEC61000-4-2(ESD) level 4, IEC 61000-4-4 (EFT) level 4, IEC 61000-4-5(Surge) level 4

Anti-vibration performance: IEC 60068-2-6

Shock resistance: IEC 60068-2-27

Free fall: IEC 60068-2-32

Note: Please go to the official website of Wintop Optical for the latest certification status.

MTBF (mean time between failures)

Time: 500000 h

Warranty

Quality assurance: 5 years

Shenzhen Wintop Optical Technology Co., LTD.

11F~12F, Senhainuo Kechuang Building, Shilongzai Community, Shiyan Street, Baoan District, Shenzhen China

Tel: +86-755-26641737

Fax: +86-755-86555405

E-mail: sales@wintoptec.com

Http: //www.wintoptec.com

Page 1 of 2


Rev 1.0

Issued Date: 2022-4-2

Fiber properties

	1000BaseFX	
	Multimode	Single mode
Wavelength	850 nm	1310/ 1550nm
Maximum transmission power	-3 dBm	0 dBm
Minimum transmission power	-8 dBm	-10 dBm
Receiving sensitivity	-19 dBm	-22 dBm
Link budget	11 dB	12 dB
Typical distance	550 m	20 km
Saturation	-3 dBm	-3 dBm

Product size (mm)



Order information	Port type			
	Optical model	10/100BaseT	10/100/1000BaseT	1000BaseFX
				Single mode Multimode
RS636-2GF4GT		—	4	2

Parking list

- Ethernet switch
- Installation accessories
- User's Manual
- Warranty Card & Conformity Certificate